LW MASS CS-424 Light Weight Multirole Stabilized System






- Laser dazzler

FEATURES

- Audio Range (ideal conditions) : 2000 meters (max)
- Sound Pressure level 151 dB A weighted at 1 m
- Beamwidth +/- 12° (24° conical @2KHz 3dB)
- Frequency response 300 Hz to 8 KHz)
- Two axes auto-stabilization
- Automatic pointing (STABILIZATION)
- Video/Audio recording
- Search light with 3500 meters range (12 Mcd remotely controlled beam)
- Laser dazzler 5000 mW (continuous or strobe mode @10 Hz)
- Laser range finder (eye safe) 1500 meters range (10 mq NATO TARGET)
- Daylight TV Camera (with 30x zoom, 0.01 lux)
- Rugged Control Console

OPTIONS

Radar Interfaceability Video Tracking Thermal Camera



TECHNICAL CHARACTERISTICS

EQUIPMENT

DIMENSION(mm) 970(H)x790(W)x690(D)
WEIGHT (Kg) 140 Approx
POWER SUPPLY

Vac 115-230 VAC Vdc 24-28 Vdc (with external inverter)

CONSUMPTION

Average during operation 400 W
Peak 1 KW
POINTING ACCURACY +/- 0.5°
ROTATION SPEED (max) 40°/sec

INTERFACES

WITH C2 (option) Ethernet 10/100 on copper

WITH AHRS (OPTION) RS-422 NMEA 0187 Protocol

Powered by



SITEP Italia SpA